

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# S2 GOLD

PRODUCT CODE  
ŠIFRA PROIZVODA

**237251G**



### TEHNIČKI PODACI

Jednoručna baterija  
Minimalistički dizajn  
Telo od mesinga  
Završna obrada - PVD brušeno zlato  
Zidna montaža  
Keramički prebacivač 180°  
Tuš ruža D.250mm - PTRUSPSG  
Keramički mešač CITEC® 25mm - PKM25SB  
S.2 GOLD tuš crevo 150cm - PGC170SG  
Tuš ručica - PTRECSG  
Protok max. 8lit/min - WaterCare

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Minimalist design  
Solid brass body  
Brushed gold PVD finish  
Wall assembly  
Ceramic diverter 180°  
Shower head D.250mm - PTRUSPSG  
CITEC®25 mm ceramic cartridge - PKM25SB  
S.2 GOLD shower hose 150cm - PGC150SG  
Hand shower - PTRECSG  
WaterCare - max flow rate 8lit/min

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

