

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 GOLD

PRODUCT CODE
ŠIFRA PROIZVODA

239101G



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - PVD brušeno zlato
Montiranje na jedan otvor
Klasa protoka Z - 7 lit/min
NEOPERL® HONEYCOMB®- PPM22N
Keramički mešač CITEC® 25mm - PKM25SA
Set za pričvršćenje sa jednim vijkom
NEOPERL® SPX® priključna creva - FB50PX

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Brushed gold PVD finish
Single hole assembly
Flow rate Z - 7 lit/min
NEOPERL® HONEYCOMB®- PPM22N
CITEC®25 mm ceramic cartridge - PKM25SA
Single screw fixing set
NEOPERL® SPX® connecting hoses - FB50PX

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

