

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 GOLD

PRODUCT CODE
ŠIFRA PROIZVODA

237351G



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - PVD brušeno zlato
Zidna montaža
Keramički prebacivač 180°
Tuš ruža D.250mm - PTRUSPSG
Keramički mešač CITEC® 25mm - PKM25SB
S.2 GOLD tuš crevo 150cm - PGC170SG
Tuš ručica - PTRECSG
Protok max. 8lit/min - WaterCare

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Brushed gold PVD finish
Wall assembly
Ceramic diverter 180°
Shower head D.250mm - PTRUSPSG
CITEC®25 mm ceramic cartridge - PKM25SB
S.2 GOLD shower hose 150cm - PGC150SG
Hand shower - PTRECSG
WaterCare - max flow rate 8lit/min

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

